

## IN THE CLAIMS

Claims 1-19 are pending in this application. Please amend claims 1, 6-8, and 11 and add new claims 13-19 as follows:

1. (Currently Amended) A sailing device suitable for use in a pleasure boat, comprising:  
a sail portion composed of a backbone, a pair of left and right spars extending obliquely backward from the fore end of the backbone and a sail-cloth attached at the fore edge thereof to the pair of left and right spars and at the aft end thereof to the aft end of the backbone[[,]and  
a strut ~~capable of being hinged at the upper end thereof to the fore end of the backbone to be~~ being movable on a pivotal point between a position extending downward from the fore end of the backbone and a position along the backbone, the lower end of said strut being directly mounted on the boat hull or indirectly attached to the boat hull by support of a user to permit rise and fall movement of the strut,  
wherein the pivotal point is near an upper end portion of the strut.
2. (Previously Presented) A sailing device as claimed in claim 1, wherein said strut is detachably mounted on the boat hull at its lower end for rise and fall movement of the strut.
3. (Previously Presented) A sailing device as claimed in claim 1, further comprising an adaptor fastened to the user's body to support the lower end of said strut for rise and fall movement of the strut.
4. (Previously Presented) A sailing device as claimed in claim 1, wherein a lateral handle is mounted to an intermediate portion of said strut for operation of the sailing device.
5. (Previously Presented) A sailing device as claimed in claim 1, wherein said sail portion has left and right wing sections each provided with a dihedral angle.
6. (Currently Amended) A sailing device ~~as claimed in claim 5,~~ suitable for use in a pleasure boat, comprising:

a sail portion composed of a backbone, a pair of left and right spars extending obliquely backward from the fore end of the backbone and a sail-cloth attached at the fore edge thereof to the pair of left and right spars and at the aft end thereof to the aft end of the backbone; and

a strut capable of being hinged at the upper end thereof to the fore end of the backbone to be movable between a position extending downward from the fore end of the backbone and a position along the backbone, the lower end of said strut being directly mounted on the boat hull or indirectly attached to the boat hull by support of a user to permit rise and fall movement of the strut,

wherein said sail portion has left and right wing sections each provided with a dihedral angle,

wherein said left and right spars are connected to each other at their intermediate portions by means of an upper tension rope, and

wherein said left and right spars are connected at their intermediate portions to an intermediate portion of said strut by means of left and right tension ropes.

7. (Currently Amended) A sailing device ~~as claimed in claim 1,~~ suitable for use in a pleasure boat, comprising:

a sail portion composed of a backbone, a pair of left and right spars extending obliquely backward from the fore end of the backbone and a sail-cloth attached at the fore edge thereof to the pair of left and right spars and at the aft end thereof to the aft end of the backbone; and

a strut capable of being hinged at the upper end thereof to the fore end of the backbone to be movable between a position extending downward from the fore end of the backbone and a position along the backbone, the lower end of said strut being directly mounted on the boat hull or indirectly attached to the boat hull by support of a user to permit rise and fall movement of the strut,

wherein said left and right spars are connected at their one ends to the fore end of said backbone for tilt movement, a slider is mounted on an intermediate portion of said backbone for slide movement in a longitudinal direction of said backbone, left and right rods are pivoted at their one ends to each intermediate portion of said spars and at their other ends to said slider, and a lower rod is pivoted at its one end to an intermediate portion of said strut and at its other end to said slider, and

wherein said slider is moveable in the longitudinal direction of said backbone to extend said spars obliquely backward from the fore end of said backbone and to fold said spars along said backbone, said slider being engageable with a stopper hook fixed to the fore portion of said backbone when said strut is unfolded downward from the fore end of said backbone and is folded along said backbone.

8. (Currently Amended) A sailing device ~~as claimed in claim 4~~, suitable for use in a pleasure boat, comprising:

a sail portion composed of a backbone, a pair of left and right spars extending obliquely backward from the fore end of the backbone and a sail-cloth attached at the fore edge thereof to the pair of left and right spars and at the aft end thereof to the aft end of the backbone; and

a strut capable of being hinged at the upper end thereof to the fore end of the backbone to be movable between a position extending downward from the fore end of the backbone and a position along the backbone, the lower end of said strut being directly mounted on the boat hull or indirectly attached to the boat hull by support of a user to permit rise and fall movement of the strut,

wherein a lateral handle is mounted to an intermediate portion of said strut for operation of the sailing device, and

wherein said handle is fixed in a lateral position when it is used and is folded along said strut when it is not used.

9. (Previously Presented) A sailing device as claimed in claim 7,

wherein an unfolding rope connected at its one end to said slider is extended forward along said backbone and extended downward along said strut through a guide pulley mounted to the fore end of said backbone to move said slider forward when a grip connected to its other end is drawn by the user, and

wherein a release rope is connected at its one end to said stopper hook to disengage said slider from said stopper hook when a grip connected to its other end is drawn by the user.

10. (Previously Presented) A sailing device as claimed in claim 7, wherein the central aft portion of said sail-cloth is detachably fastened to said backbone.
11. (Currently Amended) A sailing device ~~as claimed in claim 1~~, suitable for use in a pleasure boat, comprising:  
a sail portion composed of a backbone, a pair of left and right spars extending obliquely backward from the fore end of the backbone and a sail-cloth attached at the fore edge thereof to the pair of left and right spars and at the aft end thereof to the aft end of the backbone; and  
a strut capable of being hinged at the upper end thereof to the fore end of the backbone to be movable between a position extending downward from the fore end of the backbone and a position along the backbone, the lower end of said strut being directly mounted on the boat hull or indirectly attached to the boat hull by support of a user to permit rise and fall movement of the strut,  
wherein an upper rib pivoted at its one end to the aft portion of said backbone to be moveable between a first position where it is approached above the aft portion of said backbone and a second position where it is approached to said backbone at its front end and apart from said backbone at its rear end, and  
wherein said sail-cloth is attached at its aft end portion to the rear end of said upper rib and is detachably fastened at its central aft portion to the front end of said upper rib or said backbone at a position near the front end of said upper rib.
12. (Previously Presented) A sailing device as claimed in claim 8,  
wherein an unfolding rope connected at its one end to said slider is extended forward along said backbone and extended downward along said strut through a guide pulley mounted to the fore end of said backbone to move said slider forward when a grip connected to its other end is drawn by the user, and  
wherein a release rope is connected at its one end to said stopper hook to disengage said slider from said stopper hook when a grip connected to its other end is drawn by the user.
13. (New) A sailing device as claimed in claim 1, further comprising a head block,

wherein the head block is connected with at least one end portion of the backbone at the pivotal point and

wherein the head block is connected with the upper end portion of the strut.

14. (New) A sailing device as claimed in claim 5,

wherein said left and right spars are connected to each other at their intermediate portions by means of an upper tension rope, and

wherein said left and right spars are connected at their intermediate portions to an intermediate portion of said strut by means of left and right tension ropes.

15. (New) A sailing device as claimed in claim 1,

wherein said left and right spars are connected at their one ends to the fore end of said backbone for tilt movement, a slider is mounted on an intermediate portion of said backbone for slide movement in a longitudinal direction of said backbone, left and right rods are pivoted at their one ends to each intermediate portion of said spars and at their other ends to said slider, and a lower rod is pivoted at its one end to an intermediate portion of said strut and at its other end to said slider, and

wherein said slider is moveable in the longitudinal direction of said backbone to extend said spars obliquely backward from the fore end of said backbone and to fold said spars along said backbone, said slider being engageable with a stopper hook fixed to the fore portion of said backbone when said strut is unfolded downward from the fore end of said backbone and is folded along said backbone.

16. (New) A sailing device as claimed in claim 4, wherein said handle is fixed in a lateral position when it is used and is folded along said strut when it is not used.

17. (New) A sailing device as claimed in claim 14,

wherein an unfolding rope connected at its one end to said slider is extended forward along said backbone and extended downward along said strut through a guide pulley mounted to the fore end of said backbone to move said slider forward when a grip connected to its other end is drawn by the user, and

wherein a release rope is connected at its one end to said stopper hook to disengage said slider from said stopper hook when a grip connected to its other end is drawn by the user.

18. (New) A sailing device as claimed in claim 14, wherein the central aft portion of said sail-cloth is detachably fastened to said backbone.

19. (New) A sailing device as claimed in claim 1,  
wherein an upper rib pivoted at its one end to the aft portion of said backbone to be moveable between a first position where it is approached above the aft portion of said backbone and a second position where it is approached to said backbone at its front end and apart from said backbone at its rear end, and

wherein said sail-cloth is attached at its aft end portion to the rear end of said upper rib and is detachably fastened at its central aft portion to the front end of said upper rib or said backbone at a position near the front end of said upper rib.

20. (New) A sailing device as claimed in claim 15,

wherein an unfolding rope connected at its one end to said slider is extended forward along said backbone and extended downward along said strut through a guide pulley mounted to the fore end of said backbone to move said slider forward when a grip connected to its other end is drawn by the user, and

wherein a release rope is connected at its one end to said stopper hook to disengage said slider from said stopper hook when a grip connected to its other end is drawn by the user.